

PATENT APPLICATION

METHOD AND APPARATUS FOR MAPPING AN MPLS TAG TO A DATA PACKET IN A HEADEND

By Inventors:

Kartik Chandran
581 Tahoe Terrace
Mountain View, CA 94041
A Citizen of India

Chrisanto Leano
4626 Marbella Court
San Jose, CA 95124
A Citizen of the United States

Sunil Khaunte
3700 Lillick Drive
Santa Clara, CA 95051
A Citizen of India

Jerry D. Goodrich
7 Winterberry Lane
York, ME 04038
A Citizen of the United States

Kelly Schaefer
406 Wingate Pl SW
Leesburg, VA 20175
A Citizen of the United States

Assignee:

Cisco Technology, Inc.

Entity:

Large

METHOD AND APPARATUS FOR MAPPING AN MPLS TAG TO A DATA PACKET IN A HEADEND

5

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

The present invention relates generally to cable modem networks and provisioning cable modems. More specifically, it relates to enabling a cable
10 modem to have multiple qualities of service or ISPs without altering any configuration data at the cable modem network headend.

2. DISCUSSION OF RELATED ART

As cable modems proliferate, situations will arise in which a single cable modem must accommodate various ISPs or various levels of quality of
15 service (QOS) from a single ISP. A household may have one cable modem connected to one or more PCs or other IP-addressable devices. Members in the household will have various needs in terms of QOS, speed and other factors. For example, one member of the house may need a high QOS because he is telecommuting and his employer is paying for the comparatively high-
20 priced service. A child in the house may not need fast or the highest-QOS Internet access but rather only modest Internet access. Yet other members of the household can get along with mid-tier QOS Internet access (but will eventually want to upgrade to a better service). The telecommuter may be required to use ISP "A" because his employer requires it if they are going to
25 pay for it and the other members of the household may use ISP "B" which is

the commonly used ISP in their geographic area. Alternatively, all members of the household can use one ISP (such as ISP "A") and have different QOSs or the household can have three different ISPs. In any case, a single cable modem has to enable multiple QOSs and ISPs if necessary. It can be noted
5 that the cable modem network is deemed an open resource and thus has an open access requirement. This allows competition among the ISPs which want to provide Internet access service for cable modem users.

Presently, in order for a cable modem to handle the above scenario, changes must be made to the cable modem network operator's provisioning
10 system, i.e., the DHCP/TFTP server, *and* to the cable modem network headend, also referred to as the CMTS. The CMTS must be modified such that for each new QOS or ISP associated with a cable modem, a new virtual cable interface is created. That is, a new sub-interface under a primary cable interface needs to be created wherein, a primary cable interface is
15 implemented with one line card in the CMTS. For example, cable modems A1 through A5 using ISP "A" which services a certain range or group of IP addresses gets its own virtual or sub cable interface. Creating and managing all of the sub-interfaces, which are likely grow, at the CMTS require more work by the network operator and are error-prone operations potentially
20 disrupting service for many customers.

Associated with each data packet coming upstream from the cable modem to the CMTS is an MPLS (multiprotocol label switch) label or tag. As is known in the field of cable modem networks, the MPLS tag is used as an MPLS-VPN (virtual private network) tag as is common when a shared link is

used to send traffic. Presently, with the DOCSIS 1.0 design, the SID of the data packet is used to determine which MPLS/VPN tag is given to the data packet. Data traffic is labeled with an MPLS/VPN tag based on external criteria or policies. The traffic is then treated differently based on the MPLS/VPN tags. For example, in the cable modem network scenario, a data packet is sent upstream to the CMTS and then typically forwarded to another network, such as the Internet, via an edge router, for example. In the example above, each ISP can be assigned a unique MPLS-VPN tag that identifies traffic belong to that ISP. The MPLS-VPN tag can then be used as a basis to apply security/QoS or any other defined policies on the traffic.

Therefore, it would be desirable to enable a cable modem network to accommodate the addition of ISPs or QOS levels to a single cable modem by only having to update the provisioning system and without having to modify the CMTS. It would also be desirable to have a more efficient way to map a data packet to a MPLS/VPN tag in the CMTS. In the process, IP address management would be simplified by not having to create multiple sub-interfaces in the CMTS.

SUMMARY OF THE INVENTION

In one aspect of the present invention, a method of provisioning a cable modem in a cable modem network having a provisioning system and a headend is described. A configuration file is transferred to a cable modem from a provisioning system. At the headend or CMTS, a first data packet is received from a cable modem. This first data packet has associated with it a first service flow. In addition, the first data packet is mapped to a first sub-interface. A second data packet from the same cable modem is also received at the headend. The second data packet has a second service flow and is mapped to a second sub-interface. The first service flow and the second service flow are then derived at the headend. The first data packet is then tagged with a first MPLS tag and the second data packet is tagged with a second MPLS tag. During the entire process the headend is unmodified.

In one embodiment the configuration file is examined at the headend using a SID to determine service flow. In another embodiment, the configuration file contains multiple MPLS tags associated with multiple service flows. In yet another embodiment, vendor-specific information and MPLS data is downloaded to a configuration file before transmitting the configuration file to the cable modem. In yet another embodiment, the configuration file is modified at the provisioning system.

In another aspect of the present invention, a method of mapping an MPLS tag to a data packet in a CMTS is described. At the CMTS in a cable plant, a data packet having a SID is received. The SID is used to obtain a

service flow assigned to the data packet. An appropriate MPLS tag is then determined for the data packet based on the service flow. The data packet is then tagged with the MPLS tag before it is transmitted to an external entity.

In another aspect of the present invention, a method of enabling
5 a cable modem to service multiple quality of service levels for a data packet transmitted from one or more connected IP-addressable devices is described. A configuration file is received at the headend upon powering up of a cable modem, the configuration file containing one or more MPLS tags, an MPLS tag being associated with a service flow. A data packet is received from a
10 connected IP-addressable device and has an IP address. The IP address of the data packet is examined and a classifier is determined based on the IP address by examining the configuration file.

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

FIG. 1 is a diagram illustrating a portion of the data contained in a cable modem configuration file in accordance with one embodiment of the present invention.

Attorney Docket No. CISC212

DETAILED DESCRIPTION

Reference will now be made in detail to a preferred embodiment of the invention. An example of the preferred embodiment is illustrated in the accompanying drawings. While the invention will be described in conjunction with a preferred embodiment, it will be understood that it is not intended to limit the invention to one preferred embodiment. To the contrary, it is intended to cover alternatives, modifications, and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

10 A method of using DOCSIS 1.1 features and an enhanced version of the DOCSIS 1.0 to allow the addition of ISPs and QOS levels to a single cable modem without having to modify the CMTS is described in the various figures. Instead of using the SID of a data packet to determine the VPN tag of a data packet (DOCSIS 1.0), a service flow is used to identify the appropriate tag. As will be described below, this is done using the DOCSIS 1.1 configuration file. By doing so, the need for creating additional sub-interfaces in the cable modem interface does not arise. Instead, the configuration is modified at the provisioning server, i.e., the DHCP/TFTP server.

20 With DOCSIS 1.1 a single cable modem can have various service flows, where the service flows can be used to implement various QOS levels. Examples of QOS parameters include priorities, peak data rates and guaranteed data rates. Each service flow has a one or more specific defining packet classifiers. A classifier is defined by the network operator or

attorney docket no. CISC212

administrator. It includes filtering data based on Layer 3 and Layer 4 header data. Data packets coming from one cable modem can have different service flows and classifiers. However, with DOCSIS 1.0, data packets with different service flows go to the same sub-interface and therefore are assigned the same MPLS/VPN tag. Therefore, in DOCSIS 1.0, there is no means of distinguishing between different types of traffic, hence all traffic is mapped to the same sub-interface. This is true because all the data packets from the same cable modem have the same IP address and therefore are assigned the same tag. With the present invention, data packets having different service flows can be assigned different MPLS/VPN tags.

A number of steps occur in order for a data packet to be tagged by the appropriate MPLS/VPN tag. There is a specific configuration of the tag and a mapping of a data packet with the tag. This was previously done using the SID of the data packet. With the present invention the mapping is done using a service flow. Policies are then determined based on the MPLS/VPN tags. As is known in the field of cable modem network management, a SID for a cable modem is established in the CMTS. The CMTS knows which subinterface the data packet belongs to. This is possible because each cable modem has an IP address and using this address, it can be determined which ISP the modem is using and, therefore, which subinterface will receive and process the data packet. At this stage the MPLS/VPN tag is added to the packet, i.e., tag processing. The MPLS tag is then examined and the appropriate policies are applied to the data packet as is normally done.

Under DOCSIS 1.1 a cable modem configuration file contains various types of information. FIG. 1 is a diagram illustrating a portion of the data contained in a cable modem configuration file in accordance with one embodiment of the present invention. A cable modem configuration file 102 is sent from the provisioning system to the cable modem when the modem is first powered on. The configuration file is essentially created by the network operator/administrator. During the modem's initial provisioning stage, the same configuration file containing additional data added by the cable modem is sent to the CMTS.

File 102 contains a listing of multiple service flows 104 naming ServiceFlow 1, ServiceFlow 2, ServiceFlow 3 and so on. A service flow maps to a particular SID. For example, ServiceFlow 1 maps to SIDx, ServiceFlow 2 maps to SIDy, and so on. Each service flow also has associated with it one or more QOS parameters. Other data similar to a QOS parameter in the configuration file includes vendor-specific extension data and the MPLS/VPN tags, determined by the network operator. Each service flow (and, by association, SID) maps to one or more classifiers. A list of classifiers 106 corresponds to service flow list 104. In FIG. 1 ServiceFlow 1 maps to Classifier 1, ServiceFlow 2 maps to Classifier 2 and so on. However, more than one classifier can map to a service flow. Each classifier identifies a particular type of data traffic based on Layer 3 and 4 header data, which can be associated with a particular quality of service in the described embodiment. For example, Classifier 1 is for regular web traffic. Data on this service flow qualifies for classifier 1 if the data goes through TCP source port 80.

Classifier 2 is for data using the voice-over-IP protocol, which has a different service flow and SID, namely ServiceFlow 2 and SIDy. Thus, with DOCSIS 1.1, a configuration file for a cable modem can contain numerous service flows and SIDs. Each service flow maps to a classifier which identifies a particular quality of service. Each classifier also has an associated IP address range. This is the address range of the ISP providing service to one of the IP-addressable devices connected to the cable modem. Each ISP providing service through the cable modem has a range of IP addresses that it services. The concept of service flows mapping to classifiers for a single cable modem is a new feature in DOCSIS 1.1.

A cable modem is typically connected to one or more PCs or other IP-addressable devices. The present invention relates to sending data traffic upstream from the cable modem to the CMTS. The CMTS then sends the data to an appropriate device, such as an edge router which sends the data to the Internet. At each "stop" along the way to the packet's final destination, the MPLS/VPN tag of the data packet is checked to see what type of transmission treatment the packet should receive when the packet transits through various devices, such as routers and servers, before reaching its final destination.

FIG. 2 is a flow diagram of a process of mapping data packets to MPLS/VPN tags in accordance with one embodiment of the present invention. At step 202 a PC or Internet appliance sends data traffic, made up of multiple data packets, to a cable modem for transmission to the Internet. For the purposes of illustrating the described embodiment, operations on a single data packet going through the process are examined. A data packet having an IP

address and belonging to a particular class is sent to the cable modem. At step 204 the cable modem examines the IP address of the device from which the data packet is originating. Recall that the cable modem can be connected to numerous devices, each having a different ISP and, thus, a different IP address range. The cable modem then examines its configuration file, such as file 102, and determines which classifier the data packet belongs at step 206. Each classifier in list 106 has an IP address range. The classifier of the data packet is determined by examining within which range the IP address falls.

Once the data packet's classifier is determined using the right-hand column as shown in configuration file 102, the cable modem is able to map this information to a service flow step 208. For example, if the data packet is in classifier 2, it is mapped to ServiceFlow 2. Once the service flow is determined, a SID can be assigned to the data packet using data in the left-hand column in configuration file 102 at step 210. Each service flow has its own unique SID as shown in FIG. 1.

At this stage the data packet is transmitted upstream from the cable modem to the CMTS or headend of the cable plant at step 212. When the CMTS receives the data packet, it examines the header of the packet and reads the assigned SID. By using a configuration file similar to configuration file 102 (with additional data added by the cable modem), the CMTS uses the SID to map the data packet to a particular service flow, essentially performing the reverse of the mapping function that was performed in the cable modem at step 214. An MPLS/VPN tag is then determined based on the service flow at step 216. The configuration file contains MPLS/VPN tags for each service

flow. In the process of the present invention, the vendor-specification information and MPLS tag is downloaded to the configuration file by the network operator in the provisioning system before the configuration file is sent to the cable modem, which in turn sends it to the CMTS. The present invention adds the MPLS/VPN tag as an extra “knob” in the configuration file. Thus, the present invention describes a more flexible way to map data packets with their appropriate MPLS/VPN tags. More specifically, it does so without having to create subinterfaces in the cable interface in the CMTS and by only having to modify the provisioning system.

Although the foregoing invention has been described in some detail for purposes of clarity of understanding, it will be apparent that certain changes and modifications may be practiced within the scope of the appended claims. Furthermore, it should be noted that there are alternative ways of implementing both the process and apparatus of the present invention.

Accordingly, the present embodiments are to be considered as illustrative and not restrictive, and the invention is not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.